

Pentrunder[®]

CONCRETE CUTTING SYSTEMS

Pentrunder 3P8 HF Wire Saw

Light weight modules



Large storage capacity

Optimal force applied to the wire



Pentpak 427 HF-power pack with Pentrunder autofeed system

Safe and easy to use guards



Trouble-free start of wire

High power, high torque motor

Durable, heavy duty connectors



High performance - Reliability - Easy handling

- The Pentrunder 3P8 wire saw combines low weight with extraordinary performance and is suitable for both small and large jobs.
- Recommended for use with the 25 or 30 HP HF-motor, or hydraulic motor.
- Quick and easy setup thanks to the modular design. No module weighs more than 55 lbs.
- The start of the wire is very easy thanks to the electric automatic feed and high power of the drive motor.
- The automatic feed makes it very easy to run the saw and also extends the lifetime of the wire.
- Storage capacity up to 65 feet depending on what combination of columns are used.
- Optimal force is applied thanks to the 20 inch main drive pulley. The wire wraps around the main drive pulley over 270°, which gives superior traction.

EXCLUSIVELY AVAILABLE FROM



Diamond Tools and Equipment

ICSDIAMONDTOOLS.COM | 800.321.1240

Effective January 1, 2020 | Copyright 2020 ICS | Blount Inc. Pricing and specifications subject to change without notice. All rights reserved. Rev: 1019.
ICS, BLOUNT INC. HEADQUARTERS | 4909 SE International Way | Portland, OR 97222-4679 USA

Pentrunder 3P8 wire saw

Power

Drive motor: 400 Hz High Frequency Motor
Max continuous output power: 25 HP

Storage

Storage in rollers: 21 feet
Storage capacity: 8 feet of wire pulled in for each
1 foot travel of the carriage
Maximum approximately 65'.

Pulleys

Main drive pulley diameter: 20"
Storage pulleys diameter: 8" O.D.

Rig

Rig for wire saw with 70 mm column system:

BTC5 Base plate, fixed:	39 lbs
WT-BFC5-300 Wheel Kit	15 lbs
CN Columns: 47" / 58"	27 / 32 lbs
CE1 Carriage for 70 mm columns x 2:	21 lbs
PT-3P8 Electric feed unit:	9 lbs
FE1 Friction brake:	1 lb



Pentpak 427 HF-power pack

Input Voltage: 380-480 V
Input frequency: 50 - 60 Hz
Continuous output power: 25 HP (with 3P8 wire saw
and 30 HP HF-motor)

Minimum fuse: 16 Amp
(the "demanded" power output might need
to be reduced on the remote control.)

Recommended fuse: 40 Amp
Current draw at max. output: 56 Amp
Minimum generator capacity: 44 kVA/ 35 kW
Weight: 57 lbs

Tractive AB reserves the right to change technical data without previous notice.

Modules

Wire saw modules:

3P8-DP-HF Drive pulley, electric:	31 lbs
3P8-UA Upper assembly:	33 lbs
3P8-LA Lower assembly:	43 + 28 lbs

Guard:

3P8-DPG Guard, door main drive pulley:	11 lbs
3P8-TG Guard, storage pulleys:	20 lbs
3P8-LMG Guard, top pulleys:	23 lbs
3P8-SSG Guard, slack side channel:	14 lbs

Accessories

Satellite pulley, universal, 2-link	
WSP2-90, 90° / WSP2-180, 180°:	40 lbs
WSP1-F Satellite pulley, single:	6 lbs

System

The same HF-motor which is used for wall sawing is used for wire sawing with the Pentrunder 3P8. We recommend the 30 HP HF-motor but the 25 and 37 HP HF-motors can also be used.

EXCLUSIVELY AVAILABLE FROM



Diamond Tools and Equipment

ICSDIAMONDTOOLS.COM | 800.321.1240